

SAFETY DATA SHEET

Product: Activator for Rubber Surfaces Bufpal E

Revision: 03

Date: 07/08/2026

Pages: 1/8

1 - IDENTIFICATION

Product identifier:	Activator for Rubber Surfaces Bufpal E
Other means of identification:	480112
Recommended use of the chemical and restrictions on use:	Rubber surfaces that will receive repairs or any process involving adhesion or curing. Restrictions on use: For more information, consult the product's technical data sheet. This product should not be used for applications other than those recommended in this section.
Manufacturer's name:	Vipal Rubber Corporation
Address:	2601 NW 89, FL 33172 - Miami - FL - United States.
Telephone number:	+1 305 640 0330
Emergency phone number:	+1 305 640 0330

2 - HAZARD IDENTIFICATION

Classification of the chemical:	Flammable Liquids - Category 2; Skin Corrosion/Irritation - Category 2; Specific Target Organ Toxicity – Single Exposure - Category 3 - Narcotic.
Classification system adopted:	OSHA HCS 29 CFR 1910.1200 Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.
Pictograms:	



Signal word:	DANGER
Hazard statement(s):	Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness.
Precautionary statement(s):	PREVENTION: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection and hearing protection. RESPONSE TO EMERGENCY: If on skin: Wash with plenty of water. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or a doctor, if you feel unwell. Specific treatment. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

SAFETY DATA SHEET

Product: Activator for Rubber Surfaces Bufpal E

Revision: 03 Date: 07/08/2026 Pages: 2/8

	In case of fire: Use carbon dioxide (CO ₂), foam, water mist and powder to extinguish.
	STORAGE: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
	DISPOSITION: Dispose of contents and container in accordance with local regulations.
Other hazards which do not result in classification:	The product has no other hazards.
Any hazards not otherwise classified that have been identified during the classification process:	Hazardous to the Aquatic Environment - Acute Hazard - Category 2. Hazardous to the Aquatic Environment - Chronic Hazard - Category 2.

3 - COMPOSITION/INFORMATION ON INGREDIENTS
MIXTURE

Components contributing to the hazard:		
CAS number:	64741-42-0	
Product identifier	CAS/EC	Concentration range (%)
Naphtha (petroleum), full-range straight-run	64741-42-0 265-042-6	56.58 - 84.86

4 - FIRST-AID MEASURES

Description of necessary measures	
Inhalation:	Remove victim to fresh air and keep in a position that does not obstruct breathing. If you feel unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this document.
Skin contact:	Wash exposed skin with sufficient amount of water to remove the product. Remove and isolate contaminated clothing and shoes. In case of skin irritation: Consult a doctor. Bring this document.
Eye contact:	Rinse carefully with water for several minutes. If wearing contact lenses, remove them if it is easy and keep rinsing. If eye irritation persists: consult a doctor. Bring this document.
Ingestion:	Wash the victim's mouth with plenty of water. Never give anything by mouth to an unconscious person. If you feel unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this document.
Most important symptoms/effects, acute and delayed:	Causes skin irritation with redness, pain and dryness. May cause drowsiness or dizziness, may cause dizziness and nausea.
Indication of immediate medical attention and special treatment needed, if necessary:	Avoid contact with the product when helping the victim. If necessary, symptomatic treatment should include, above all, supportive measures such as correction of hydro electrolytic and metabolic disorders and respiratory assistance. In case of skin contact, do not rub the affected area.

5 - FIRE-FIGHTING MEASURES

Extinguishing media:	Suitable: carbon dioxide (CO ₂), foam, water mist and powder. Unsuitable: water directly onto the burning material.
----------------------	--

SAFETY DATA SHEET

Product: Activator for Rubber Surfaces Bufpal E

Revision: 03	Date: 07/08/2026	Pages: 3/8
Specific hazards arising from the chemical:	Combustion of the material or its packaging can form irritating and toxic gases such as carbon monoxide and dioxide. Very dangerous when exposed to excessive heat or other sources of ignition such as: sparks, open flames or flames from matches and cigarettes, welding operations, pilot lights and electric motors. May build up static charge by flow or agitation. Vapors from heated product can ignite by static discharge. Vapors are denser than air and tend to accumulate in low-lying or confined areas such as storm drains and basements. It can travel great distances causing the flame to retreat or new fires in both open and confined environments. Containers may explode if heated.	
Special protective actions for fire-fighters:	If the load is involved in fire, isolate and evacuate the area to a minimum radius of 800 meters. Wear positive pressure self-contained breathing apparatus (SCBA) and full protective clothing. Containers and tanks involved in the fire must be cooled with water mist.	

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures:	For non-emergency personnel: Isolate the leak from sources of ignition. Keep unauthorized persons away from the area. Stop the leak if it can be done without risk. Prevent sparks or flames. Do not smoke. Do not touch damaged containers or spilled product unless wearing suitable clothing. Avoid exposure to the product. Stay in a safe place with the wind at your back. Use personal protective equipment as described in section 8. For emergency responders: Use full PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In the event of a leak, where exposure is high, the use of an appropriate respiratory protection mask is recommended. Emergency procedures: Prevent spilled product from reaching watercourses and sewage systems.	
Methods and materials for containment and cleaning up:	Use water mist to reduce vapor dispersion. Use natural or spill containment barriers. Collect spilled product and place in appropriate containers. Absorb remaining product with dry sand, earth, vermiculite, or any other inert material. Place adsorbed product in appropriate containers and remove them to a safe location. Use non-sparking tools to collect absorbed product. All equipment used for handling must be electrically grounded. For final disposal, proceed as per Section 13 of this document.	

7 - HANDLING AND STORAGE

Precautions for safe handling:	Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation. Handling the product can result in electrostatic charge buildup. All ignition sources must be extinguished from areas during use. Use proper grounding procedures. Use personal protective equipment as described in section 8. Avoid contact with incompatible materials. Wash hands and face thoroughly after handling and before eating, drinking, smoking, or using the toilet. Contaminated clothing should be changed and washed before reuse. Remove contaminated clothing and protective equipment before entering eating areas. Keep away from heat, sparks, open flame, and hot surfaces. Do not smoke. Keep the container tightly closed. Ground the container vessel and product receiver during transfers. Only use non-sparking tools. Avoid the accumulation of electrostatic charges. Use explosion-proof electrical, ventilation, and lighting equipment.	
Conditions for safe storage, including any incompatibilities:	Store in a dry, well-ventilated place away from sunlight. Keep the container closed. It is not necessary addition of stabilizers and antioxidants to ensure the durability. Packaging compatibilities: Similar to the original packaging. Keep away from incompatible materials.	

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters		
Occupational exposure limit:	No occupational exposure limits are established.	
Biological limit:	No biological indicators of exposure are established.	

SAFETY DATA SHEET

Product: Activator for Rubber Surfaces Bufpal E

Revision: 03	Date: 07/08/2026	Pages: 4/8
--------------	------------------	------------

Other limits and values: No other limits and values are established.

Appropriate engineering controls: A risk assessment is recommended to define the engineering control measures necessary to eliminate or minimize the risk. These measures help to reduce exposure to the product.**Individual protection measures, such as personal protective equipment (PPE)**

Hand protection: Nitrile gloves.

Eye protection: Fully enclosed protective goggles.

Skin protection: Impervious clothing or protective clothing chemically resistant to the product.

Respiratory protection: Semifacial mask with filter for organic vapors.

9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid.

Color: Colorless.

Odor: Characteristic.

Melting point/freezing point: Not available.

Boiling point (or initial boiling point or boiling range): Not available.

Flammability: Flammable.

Lower and upper explosion limit/flammability limit: Not available.

Flash point: -35 °C (-31 °F) - Closed cup.

Auto-ignition temperature: - Naphtha (petroleum), full-range straight-run: 280 to 470 °C (536 to 878 °F).

Decomposition temperature: Not available.

pH: Not available.

Kinematic viscosity: Not available.

Solubility: Immiscible in water.

Partition coefficient n-octanol/water (log value): - Naphtha (petroleum), full-range straight-run: log K_{ow} : 1.99 to 18.02 (calculated).Vapor pressure: - Naphtha (petroleum), full-range straight-run: ≤ 240 kPa at 37.8 °C (100.04 °F).

Density and/or relative density: 0.66 to 0.73 (water at 4 °C(39.2 °F) = 1) at 20 °C (68 °F).

Relative vapor density: Not available.

Particle characteristics: Not applicable.

Other information: Not applicable.

SAFETY DATA SHEET

Product: Activator for Rubber Surfaces Bufpal E

Revision: 03

Date: 07/08/2026

Pages: 5/8

10 - STABILITY AND REACTIVITY

Reactivity: Reactivity is not to be expected under normal conditions of temperature and pressure.

Chemical stability: Stable under normal temperature and pressure conditions.

Possibility of hazardous reactions, including those associated with foreseeable emergencies: There are not known hazardous reactions with the product.

Conditions to avoid: High temperatures. Ignition sources. Contact with incompatible materials.

Incompatible materials: Oxidizing agents.

Hazardous decomposition products: No dangerous decomposition products are known.

11 - TOXICOLOGICAL INFORMATION

Symptoms related to the physical, chemical and toxicological characteristics: Causes skin irritation with redness, pain and dryness. May cause drowsiness or dizziness, may cause dizziness and nausea.

Delayed and immediate effects and also chronic effects from short and long-term exposure

Acute toxicity: Product not classified as acute toxic by oral and inhalation.
ATEmix Oral: > 5000 mg/kg.
ATEmix Vapours (4h): > 20 mg/L.

Skin corrosion/irritation: Causes skin irritation with redness, pain and dryness.

Eye damage/irritation: It is not expected to cause eye irritation.

Respiratory or skin sensitization: It is not expected to present respiratory or skin sensitization.

Germ cell mutagenicity: Not classified for germ cell mutagenicity.

Carcinogenicity: Not classified for carcinogenicity.

Reproductive toxicity: Not classified for reproductive toxicity.

Specific target organ toxicity (single exposure): May cause drowsiness or dizziness, may cause dizziness and nausea.

Specific target organ toxicity (repeated exposure): It is not expected to exhibit specific target organ toxicity on repeated exposure.

Aspiration hazard: It is not expected to present an aspiration hazard.

12 - ECOLOGICAL INFORMATION

Ecotoxicity: Not classified according to the used criteria, however, it presents relevant data, as described below.

Persistence and degradability: Although it is not possible to conclude that it is rapidly degradable, it is not expected to persist in the environment.

SAFETY DATA SHEET

Product: Activator for Rubber Surfaces Bufpal E

Revision: 03	Date: 07/08/2026	Pages: 6/8
Bioaccumulative potential:	Presents high bioaccumulative potencial in aquatic organisms. Information regarding to: - <u>Naphtha (petroleum), full-range straight-run:</u> BCF: 0.4 to 6280 log K_{ow} : 1.99 to 18.02 (calculated).	
Mobility in soil:	Not determined.	
Other adverse effects:	No other environmental effects known.	

13 - DISPOSAL CONSIDERATIONS

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:	Must be disposed of as waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product. Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.
---	---

14 - TRANSPORT INFORMATION**International regulations**

Road:	DOT - U.S. Department of Transportation.- Code of Federal Regulations.
UN number:	1268
UN proper shipping name:	PETROLEUM DISTILLATES, N.O.S.
Transport hazard class(es):	3
Packing group:	II
Environmental hazards:	The product is considered dangerous for the environment for land transport.
Sea:	IMO - International Maritime Organization: • IMDG Code - International Maritime Dangerous Goods Code.
UN number:	1268
UN proper shipping name:	PETROLEUM DISTILLATES, N.O.S.
Transport hazard class(es):	3
Packing group:	II
Environmental hazards:	The product is considered a marine pollutant.
EmS:	F-E, S-E
Air:	IATA - International Air Transport Association: • DGR - Dangerous Goods Regulation.
UN number:	1268
UN proper shipping name:	PETROLEUM DISTILLATES, N.O.S.

SAFETY DATA SHEET

Product: Activator for Rubber Surfaces Bufpal E

Revision: 03	Date: 07/08/2026	Pages: 7/8
Transport hazard class(es):	3	
Packing group:	II	
Environmental hazards:	The product is considered dangerous for the environment for air transport.	
Transport in bulk (according to IMO instruments):	Consult regulations: • International Maritime Organization: MARPOL: Articles, protocols, annexes, unified interpretations of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto, consolidated edition. IMO, London, 2006; • International Maritime Organization: IBC code: International code for the construction and equipment of shipping carrying dangerous chemicals in bulk: With Standards and guidelines relevant to the code. IMO, London, 2007.	
Special precautions for user:	Not applicable.	

15 - REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product in question:	Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.
	TSCA: We certify that all the components of this product are listed on the TSCA Inventory Active.
	Prop.65: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm. For more information go to www.P65Warnings.ca.gov .

16 - Other information, including date of preparation or last revision

This document was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other products, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

Change control:

Version	Manufacture date	Changes
03	07/08/2026	Change in section: 9.

Abbreviations:

ACGIH - American Conference of Governmental Industrial Hygienists;
ATEmix - Acute Toxicity Estimate of the mixture;
BCF - Bioconcentration factor;
CAS - Chemical Abstracts Service;
K_{ow}- Octanol-water partition coefficient;
OSHA - Occupational Safety & Health Administration;
PBT - Persistent, bioaccumulative and toxic;
UN - United Nations;
vPvB - Very Persistent and very Bioaccumulative.

In compliance with OSHA HCS 29 CFR 1910.1200

SAFETY DATA SHEET

Product: Activator for Rubber Surfaces Bufpal E

Revision: 03

Date: 07/08/2026

Pages: 8/8

Bibliographic references:

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents & Biological Exposure Indices (BEIs®). Cincinnati-USA, 2026.

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 10th rev. ed. New York and Geneva: United Nations, 2023.