

## SAFETY DATA SHEET

**Product:** CV-00 Vulcanizing Cement, CV-01 Vulcanizing Cement, CV-02 Vulcanizing Cement, BV-01 Vulcanizing Cement, BV-02 Vulcanizing Cement, BV-03 Vulcanizing Cement, Vulcanizing Cement

Revision: 05

Date: 11/03/2025

Pages: 1/10

### SECTION 1: IDENTIFICATION

**GHS product identifier:** CV-00 Vulcanizing Cement, CV-01 Vulcanizing Cement, CV-02 Vulcanizing Cement, BV-01 Vulcanizing Cement, BV-02 Vulcanizing Cement, BV-03 Vulcanizing Cement, Vulcanizing Cement

**Other means of identification:** 470008, 470010, 470011, 470012, 470036, 470021, 470022, 470023

**Recommended use of the chemical and restrictions on use:** Adhesive glue used for applying cold patches to inner tubes and cold patches to the inside of tires.  
**Restrictions on use:** This product should not be used for applications other than those recommended in this section.  
 Remove all sources of ignition. Keep away from heat, open flames, hot surfaces, sparks, and do not smoke.

For more information, consult the product data sheet.

**Supplier's details:** BORRACHAS VIPAL S.A  
**Address:** Rua Buarque de Macedo, 365, CEP: 95320-000 - Nova Prata - RS - Brasil.  
**Phone number:** (54) 3242-3800  
**E-mail:** vipal@vipal.com.br

**Emergency phone number:** (54) 3242-3800

### SECTION 2: HAZARD IDENTIFICATION

**Classification of the substance or mixture:** Flammable Liquids - Category 2;  
 Acute Toxicity - Dermal - Category 5;  
 Skin Corrosion/Irritation - Category 2;  
 Serious eye damage/eye irritation - Category 2A;  
 Reproductive Toxicity - Category 2;  
 Specific Target Organ Toxicity – Single Exposure - Category 3 - Narcotic and Category 3 - Respiratory;  
 Hazardous to the Aquatic Environment - Acute Hazard - Category 2;  
 Hazardous to the Aquatic Environment - Chronic Hazard - Category 2.

**Classification system adopted:** Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.

#### GHS label elements, including precautionary statements

**Pictograms:**



**Signal word:** DANGER

**Hazard statement(s):** H225 Highly flammable liquid and vapour.  
 H313 May be harmful in contact with skin.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H361 Suspected of damaging fertility or the unborn child.

**SAFETY DATA SHEET**

**Product:** CV-00 Vulcanizing Cement, CV-01 Vulcanizing Cement, CV-02 Vulcanizing Cement, BV-01 Vulcanizing Cement, BV-02 Vulcanizing Cement, BV-03 Vulcanizing Cement, Vulcanizing Cement

Revision: 05

Date: 11/03/2025

Pages: 2/10

	H411 Toxic to aquatic life with long lasting effects.
<b>Precautionary statement(s):</b>	<p><b>PREVENTION:</b> P203 Obtain, read and follow all safety instructions before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P264 + P265 Wash hands thoroughly after handling. Do not touch eyes. P271 Use only outdoors or with adequate ventilation. P273 Avoid release to the environment. P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.</p> <p><b>RESPONSE TO EMERGENCY:</b> P302 + P317 IF ON SKIN: Get medical help. P302 + P352 IF ON SKIN: Wash with plenty of water. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower]. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P318 IF exposed or concerned, get medical advice. P319 Get medical help if you feel unwell. P321 Specific treatment. P332 + P317 If skin irritation occurs: Get medical help. P337 + P317 If eye irritation persists: Get medical help. P362 + P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use carbon dioxide (CO<sub>2</sub>), foam, water mist and powder to extinguish. P391 Collect spillage.</p> <p><b>STORAGE:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.</p> <p><b>DISPOSITION:</b> P501 Dispose of contents and container in accordance with local regulations.</p>
<b>Other hazards which do not result in classification:</b>	The product has no other hazards.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS  
MIXTURE**

## SAFETY DATA SHEET

**Product:** CV-00 Vulcanizing Cement, CV-01 Vulcanizing Cement, CV-02 Vulcanizing Cement, BV-01 Vulcanizing Cement, BV-02 Vulcanizing Cement, BV-03 Vulcanizing Cement, Vulcanizing Cement

Revision: 05

Date: 11/03/2025

Pages: 3/10

Components contributing to the hazard:

Product identifier	CAS/EC	Concentration range (%)
Distillates (petroleum), c6-rich	93165-19-6 296-903-4	43.92 - 65.88
Methyl ethyl ketone	78-93-3 201-159-0	24.00 - 36.00
Zinc bis(n-ethyl-n-phenyldithiocarbamate)	14634-93-6 238-677-1	1.74 - 2.62
Cyclohexyl(ethyl)amine	5459-93-8	1.16 - 1.74

### SECTION 4: FIRST-AID MEASURES

#### Description of necessary first-aid measures

Inhalation:	Remove victim to fresh air and keep in a position that does not obstruct breathing. If you feel unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this document.
Skin:	Wash exposed skin with sufficient amount of water to remove the product. Remove and isolate contaminated clothing and shoes. In case of skin irritation: Consult a doctor. Bring this document.
Eye:	Rinse carefully with water for several minutes. If wearing contact lenses, remove them if it is easy and keep rinsing. If eye irritation persists: consult a doctor. Bring this document.
Ingestion:	Wash the victim's mouth with plenty of water. Never give anything by mouth to an unconscious person. If you feel unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this document.
Most important symptoms/effects, acute and delayed:	Causes skin irritation with redness, pain and dryness. Causes serious eye irritation with redness and pain. May be harmful in contact with skin. May cause drowsiness or dizziness, may cause dizziness and nausea. May cause respiratory irritation, may cause cough and sneezing.
Indication of immediate medical attention and special treatment needed, if necessary:	Avoid contact with the product when helping the victim. If necessary, symptomatic treatment should include, above all, supportive measures such as correction of hydro electrolytic and metabolic disorders and respiratory assistance. In case of skin contact, do not rub the affected area.

### SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media:	Suitable: carbon dioxide (CO <sub>2</sub> ), foam, water mist and powder. Unsuitable: water directly onto the burning material.
Specific hazards arising from the chemical:	Combustion of the material or its packaging can form irritating and toxic gases such as carbon monoxide and dioxide. Very dangerous when exposed to excessive heat or other sources of ignition such as: sparks, open flames or flames from matches and cigarettes, welding operations, pilot lights and electric motors. May build up static charge by flow or agitation. Vapors from heated product can ignite by static discharge. Vapors are denser than air and tend to accumulate in low-lying or confined areas such as storm drains and basements. It can travel great distances causing the flame to retreat or new fires in both open and confined environments. Containers may explode if heated.
Special protective actions for fire-fighters:	If the load is involved in fire, isolate and evacuate the area to a minimum radius of 800 meters. Wear positive pressure self-contained breathing apparatus (SCBA) and full protective clothing. Containers and tanks involved in the fire must be cooled with water mist.

**SAFETY DATA SHEET**

**Product:** CV-00 Vulcanizing Cement, CV-01 Vulcanizing Cement, CV-02 Vulcanizing Cement, BV-01 Vulcanizing Cement, BV-02 Vulcanizing Cement, BV-03 Vulcanizing Cement, Vulcanizing Cement

Revision: 05

Date: 11/03/2025

Pages: 4/10

**SECTION 6: ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel:	Isolate the leak from sources of ignition. Keep unauthorized persons away from the area. Stop the leak if it can be done without risk. Prevent sparks or flames. Do not smoke. Do not touch damaged containers or spilled product unless wearing suitable clothing. Avoid exposure to the product. Stay in a safe place with the wind at your back. Use personal protective equipment as described in section 8.
For emergency responders:	Use full PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In the event of a leak, where exposure is high, the use of an appropriate respiratory protection mask is recommended.
Environmental precautions:	Prevent spilled product from reaching watercourses and sewage systems.
Methods and materials for containment and cleaning up:	Use water mist to reduce vapor dispersion. Use natural or spill containment barriers. Collect spilled product and place in appropriate containers. Absorb remaining product with dry sand, earth, vermiculite, or any other inert material. Place adsorbed product in appropriate containers and remove them to a safe location. Use non-sparking tools to collect absorbed product. All equipment used for handling must be electrically grounded. For final disposal, proceed as per Section 13 of this document.

**SECTION 7: HANDLING AND STORAGE****Precautions for safe handling**

Precautions for safe handling:	Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation. Handling the product can result in electrostatic charge buildup. All ignition sources must be extinguished from areas during use. Use proper grounding procedures. Use personal protective equipment as described in section 8. Avoid contact with incompatible materials.
General hygiene:	Wash hands and face thoroughly after handling and before eating, drinking, smoking, or using the toilet. Contaminated clothing should be changed and washed before reuse. Remove contaminated clothing and protective equipment before entering eating areas.

**Conditions for safe storage, including any incompatibilities**

Technical measures for prevention of fire and explosion:	Keep away from heat, sparks, open flame, and hot surfaces. Do not smoke. Keep the container tightly closed. Ground the container vessel and product receiver during transfers. Only use non-sparking tools. Avoid the accumulation of electrostatic charges. Use explosion-proof electrical, ventilation, and lighting equipment.
Conditions for safe storage, including any incompatibilities:	Store in a dry, well-ventilated place away from sunlight. Keep the container closed. It is not necessary addition of stabilizers and antioxidants to ensure the durability. This material may react dangerously with some incompatible materials as outlined in Section 10. Keep away from incompatible materials.
Packaging compatibilities:	Similar to the original packaging.
Inadequate packaging materials:	There are not known unsuitable material.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters**

Occupational exposure	The values below apply to workplaces.
-----------------------	---------------------------------------

**SAFETY DATA SHEET**

**Product:** CV-00 Vulcanizing Cement, CV-01 Vulcanizing Cement, CV-02 Vulcanizing Cement, BV-01 Vulcanizing Cement, BV-02 Vulcanizing Cement, BV-03 Vulcanizing Cement, Vulcanizing Cement

Revision: 05

Date: 11/03/2025

Pages: 5/10

**limit:**- Methyl ethyl ketone:OSHA - PEL - TWA: 200 ppm (590 mg/m<sup>3</sup>) (29 CFR 1910.1000 Table Z-1) (CFR);NIOSH - REL - TWA: 200 ppm (500 mg/m<sup>3</sup>);NIOSH - REL - STEL: 300 ppm (885 mg/m<sup>3</sup>);

ACGIH - TLV - TWA: 75 ppm (\*);

ACGIH - TLV - STEL: 150 ppm (\*);

- Benzene:

OSHA - PEL - TWA: 1 ppm (29 CFR 1910.1028, Benzene; 29 CFR 1910.1000 Table Z-2) (CFR);

OSHA - PEL - STEL: 5 ppm (29 CFR 1910.1028, Benzene; 29 CFR 1910.1000 Table Z-2) (CFR);

NIOSH - REL - TWA: 0.1 ppm (Ca) (AA);

NIOSH - REL - STEL: 1 ppm (Ca) (AA);

ACGIH - TLV - TWA: 0.02 ppm (\*).

\*: Also absorbed through the skin;

CFR: See mentioned item in OSHA CFR;

Ca: Potential occupational carcinogen.

AA: See NIOSH REL Appendix A.

**Biological limit:**- Methyl ethyl ketone:

ACGIH - BEI: Determinant: Methyl Ethyl Ketone in Urine. Sampling Time: End of shift. Index: 2 mg/L. Notation: Ns.

- Benzene:

ACGIH - BEI: Determinant: S-phenylmercapturic acid in urine. Sampling time: End of shift. Index: 25 µg/g creatinine. Notation: B. Determinant: t,t-muconic acid in urine. Sampling time: End of shift. Index: 500 µg/g creatinine. Rating: B.

Ns: The determinant is nonspecific, since it is also observed after exposure to other chemicals;

B: The determinant may be present in biological specimens collected from subjects who have not been occupationally exposed, at a concentration which could affect the interpretation of the results. Such background concentrations are incorporated in the BEI value.

**Other limits and values:**- Methyl ethyl ketone:

IDLH (NIOSH, 2010): 3000 ppm

- Benzene:

Benzene does not have LT, but is the object of Annex 13-A, of NR15, where, for companies subject to the provisions of the Annex, the parameter VRT-MPT (average concentration of benzene in the air weighted by the time, for a working hours of eight hours, obtained in the breathing zone of workers, individually or from Homogeneous Exposure Groups - GHE, as defined in Normative Instruction No. 01). According to this Annex, the values established for the VRT-MPT are 1.0 ppm for the companies included in the Annex, with the exception of steel companies, and 2.5 ppm for the steel companies.

**Appropriate engineering controls:**

A risk assessment is recommended to define the engineering control measures necessary to eliminate or minimize the risk. These measures help to reduce exposure to the product. Maintain atmospheric concentrations of the constituents of the material below occupational exposure limits indicated.

**Individual protection measures, such as personal protective equipment (PPE)****Eye/face protection:** Fully enclosed protective goggles.**Skin protection:** Impervious clothing or protective clothing chemically resistant to the product. Nitrile gloves.

**SAFETY DATA SHEET**

**Product:** CV-00 Vulcanizing Cement, CV-01 Vulcanizing Cement, CV-02 Vulcanizing Cement, BV-01 Vulcanizing Cement, BV-02 Vulcanizing Cement, BV-03 Vulcanizing Cement, Vulcanizing Cement

Revision: 05

Date: 11/03/2025

Pages: 6/10

Respiratory protection: Half face mask with filter against organic vapors.

Thermal hazards: It does not present thermal hazards.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical state: Liquid, viscous.

Colour: Light beige.

Odour: Feature.

Melting point/freezing point: Not available.

Boiling point or initial boiling point and boiling range: 58 to 79 °C (136.4 to 174.2 °F).

Flammability: Flammable.

Lower and upper explosion limit/flammability limit: Upper: 12.6 % and Lower: 1.1 %.

Flash point: -35 °C (-31 °F) - Closed cup.

Auto-ignition temperature: 225 °C (437 °F).

Decomposition temperature: Not available.

pH: Not available.

Kinematic viscosity: Not available.

Solubility: Immiscible in water.

Partition coefficient n-octanol/water (log value): Not available.

Vapour pressure: 18 kPa at 20 °C (68 °F).

Density and/or relative density: Absolute density: 0.71 to 0.74 g/cm<sup>3</sup>.

Relative vapour density: 2.41 to 3 (Air = 1).

Particle characteristics: Not applicable.

Other information: Dynamic viscosity: 1700 to 3000 cP (1.7 to 3 Pa.s).  
Vapor pressure: 105 mbar (butanone).

**SECTION 10: STABILITY AND REACTIVITY**

Reactivity: Reactivity is not to be expected under normal conditions of temperature and pressure.

## SAFETY DATA SHEET

**Product:** CV-00 Vulcanizing Cement, CV-01 Vulcanizing Cement, CV-02 Vulcanizing Cement, BV-01 Vulcanizing Cement, BV-02 Vulcanizing Cement, BV-03 Vulcanizing Cement, Vulcanizing Cement

Revision: 05

Date: 11/03/2025

Pages: 7/10

Chemical stability:	Stable under normal temperature and pressure conditions.
Possibility of hazardous reactions:	- <u>Methyl ethyl ketone</u> : Risk of explosion on contact with hydrogen peroxide / nitric acid and hydrogen peroxide / sulfuric acid. The substance may react dangerously with oxidizing agents, trichloromethane / alkali and chromium trioxide.
Conditions to avoid:	High temperatures. Ignition sources. Contact with incompatible materials.
Incompatible materials:	Alkali, chromium trioxide, hydrogen peroxide, inorganic acids, oxidizing agents, Oxidizing materials and trichloromethane.
Hazardous decomposition products:	No dangerous decomposition products are known.

### SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity:	Product not classified as acute toxic by oral and inhalation. May be harmful in contact with skin. ATEmix Oral: > 5000 mg/kg. LD <sub>50</sub> Dermal (rats): > 2000 - ≤ 5000 mg/kg. ATEmix Vapours (4h): > 20 mg/L.
Skin corrosion/irritation:	Causes skin irritation with redness, pain and dryness.
Serious eye damage/irritation:	Causes serious eye irritation with redness and pain.
Respiratory or skin sensitization:	It is not expected to present respiratory or skin sensitization.
Germ cell mutagenicity:	Not classified for germ cell mutagenicity. This classification is due to the possibility of this product containing benzene in a concentration equal to 0.1%. However, if this value is lower, the product will not be classified as mutagenic.
Carcinogenicity:	Not classified for carcinogenicity. This classification is due to the possibility of this product containing benzene in a concentration equal to 0.1%. However, if this value is lower, the product will not be classified as carcinogenic.
Reproductive toxicity:	Suspected of damaging fertility or the unborn child.
STOT - Single exposure:	May cause drowsiness or dizziness, may cause dizziness and nausea. May cause respiratory irritation, may cause cough and sneezing.
STOT - Repeated exposure:	It is not expected to exhibit specific target organ toxicity on repeated exposure.
Aspiration hazard:	It is not expected to present an aspiration hazard.

### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:	Toxic to aquatic life with long lasting effects.  Information regarding to: - <u>Distillates (petroleum), c6-rich</u> : ErC <sub>50</sub> ( <i>Pseudokirchneriella subcapitata</i> , 96 h): 3.1 mg/L; EC <sub>50</sub> ( <i>Daphnia magna</i> , 48 h): 4.5 mg/L; LC <sub>50</sub> ( <i>Pimephales promelas</i> , 96 h): 8.2 mg/L.
--------------	---

## SAFETY DATA SHEET

**Product:** CV-00 Vulcanizing Cement, CV-01 Vulcanizing Cement, CV-02 Vulcanizing Cement, BV-01 Vulcanizing Cement, BV-02 Vulcanizing Cement, BV-03 Vulcanizing Cement, Vulcanizing Cement

Revision: 05

Date: 11/03/2025

Pages: 8/10

- Zinc bis(n-ethyl-n-phenyldithiocarbamate):

LC<sub>50</sub> (*Danio rerio*, 96 h): > 100 mg/L;

NOEC (*Desmodesmus subspicatus*, 72h): > 1 mg/L;

ErC<sub>50</sub> (Green algae, 72 h): > 4.3 mg/L;

EC<sub>50</sub> (*Daphnia magna*, 48 h): 0.0487 mg/L.

Persistence and  
degradability:

It is expected that the product presents persistence and it is not considered readily biodegradable.

Information regarding to:

- Methyl ethyl ketone:

Biodegradation rate: 98% in 28 days.

- Zinc bis(n-ethyl-n-phenyldithiocarbamate):

Degradability rate: 0% in 28 days.

Bioaccumulative  
potential:

It is not expected to have a high bioaccumulative potential.

Mobility in soil:

Not determined.

Other adverse effects:

No other environmental effects known.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### Disposal methods

Must be disposed of as waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product.

Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.

### SECTION 14: TRANSPORT INFORMATION

**Road:**

UN - United Nations: Model Regulations:

• Recommendations on the Transport of Dangerous Goods.

UN number:

1133

UN proper shipping  
name:

ADHESIVES

Transport hazard  
class(es):

3

Packing group:

II

Environmental hazards:

The product is considered dangerous for the environment for land transport.

**Railway regulations:**

COTIF - Convention concerning International Carriage by Rail:

• Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods  
by Rail.

UN number:

1133

UN proper shipping  
name:

ADHESIVES

Transport hazard  
class(es):

3



## SAFETY DATA SHEET

**Product:** CV-00 Vulcanizing Cement, CV-01 Vulcanizing Cement, CV-02 Vulcanizing Cement, BV-01 Vulcanizing Cement, BV-02 Vulcanizing Cement, BV-03 Vulcanizing Cement, Vulcanizing Cement

Revision: 05

Date: 11/03/2025

Pages: 10/10

chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

**Change control:**

Version	Manufacture date	Changes
05	11/03/2025	Change in section: 1, 10 and 12.

**Abbreviations:**

ACGIH - American Conference of Governmental Industrial Hygienists;  
ATEmix - Acute Toxicity Estimate of the mixture;  
BEI - Biological Exposure Index;  
CAS - Chemical Abstracts Service;  
EC<sub>50</sub>- Effective concentration of substance that causes 50 % of the maximum response;  
ErC<sub>50</sub>- Effective concentration that results in a 50% reduction in the growth rate;  
IARC - International Agency for Research on Cancer;  
IDLH - Immediately Dangerous to Life or Health;  
LC<sub>50</sub>- Lethal Concentration 50%;  
LD<sub>50</sub>- Lethal Dose 50%;  
NIOSH - National Institute for Occupational Safety and Health;  
NOEC - No Observed Effect Concentration;  
OSHA - Occupational Safety & Health Administration;  
PBT - Persistent, bioaccumulative and toxic;  
PEL - Permissible Exposure Limit;  
REL - Recommended Exposure Limit;  
STEL - Short Term Exposure Limit;  
TLV - Threshold Limit Value;  
TWA - Time Weighted Average;  
UN - United Nations;  
vPvB - Very Persistent and very Bioaccumulative.

**Bibliographic references:**

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents & Biological Exposure Indices (BEIs®). Cincinnati-USA, 2025.

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 10th rev. ed. New York and Geneva: United Nations, 2023.